

ESTone.tex System for theming of stone, rocks, bricks, woods, etc...

## Data Base EST-Desmoldeante

MATERIAL CLASS	EST-Liquid release agent based on mineral oils that is applied to the silicone, resin or PVC molds of the ESTone.tex System to avoid adhesion with the applied mortars.
PROPERTIES	<ul style="list-style-type: none"> <li>- It allows to obtain excellent surfaces in sight, with sharp edges, without stains peeling, or areas to retouch</li> <li>- Facilitates the stripping of molds or formwork pieces (wood, polystyrene, metal, plastics, etc ...).</li> <li>- Facilitates the cleaning of used molds or formwork.</li> <li>- Extends the useful life of the molds, as it protects them from the degrading action of mortars and their components.</li> </ul>
ADVANTAGE	<ul style="list-style-type: none"> <li>- Quick and clean application.</li> <li>- Facilitates cleaning of molds or formwork and reduces wear on the themselves.</li> <li>- Does not leave stains on ESTone.tex mortars or on the molds used.</li> </ul>
FIELDS OF USE	EST-Desmoldeante is mainly used in thematization, due to its high versatility and compatibility with the ESTone.tex System, both on vertical and horizontal surfaces. Used in construction, formwork and molds as a separator for poured or thixotropic surfaces.
APPLICATION	It is applied directly with a brush, roller or sprayer in the molds and / or directly on the surface of the newly applied mortar without influencing its qualities. It comes ready to be used and once applied it maintains its release properties for days.
COLOR	Amber.
PERFORMANCE	Approximately 12.0 to 15.0 m <sup>2</sup> / l (Consumption: 0.07 to 0.08 l / m <sup>2</sup> ).
TYPE	Liquid based on mineral oils.
DENSITY	0,84 kg/l approx.
STORAGE	12 months in its original well closed container, indoors, in a cool, dry place.
PACKING	Boats of 2 and 25 liters.
PRECAUTIONS	Shake the product before use. Flammable.
SECURITY	Before applying, always consult the labeling and the data sheet of safety for correct handling. Do not eat. Keep out of reach of children. Wear rubber gloves and goggles. Do not breathe vapors. Provide good ventilation. In case of contact with the eyes, wash them with plenty of water and see a doctor.
WASTE	Only completely empty containers will be disposed of for recycling as packaging. The excess liquid materials must be removed by a manager specialized. In any case, always review and respect current legislation and applicable in each country or region.